



CONTENTS

LIST OF FIGURES	x
LIST OF TABLES	xvii
NOMENCLATURE	xviii
CHAPTER 1. INTRODUCTION	1
1.1 Research topic, relevance and motivation	1
1.2 History of modeling two-phase flow in porous media	2
1.3 Review of literature and related work	3
1.3.1 Experimental work	3
1.3.2 Numerical work	5
1.4 Research objectives	11
1.5 Thesis outline	13
CHAPTER 2. MATHEMATICAL FORMULATION	15
2.1 Local thermal equilibrium model.....	15
2.1.1 Original enthalpy formulation of two-phase mixture model	16
2.1.2 Volumetric enthalpy formulation of two-phase mixture model	32
2.1.3 Modified volumetric enthalpy formulation of two-phase mixture model.....	34
2.1.4 Modified enthalpy formulation	43
2.1.5 Issues related to variable properties	46
2.1.6 General remarks on variants of two-phase mixture model	48
2.2 Non-dimensionalization	49
2.2.1 Modified volumetric enthalpy formulation of two-phase mixture model	49
2.2.2 Modified enthalpy formulation	54
2.3 Special treatment for diffusion coefficient	55
2.4 Local thermal non-equilibrium model	61
2.5 Anisotropic properties of porous medium model	64
2.6 Conclusions	67
CHAPTER 3. NUMERICAL METHOD	68
3.1 Discretization schemes	68
3.2 Grid layouts	69
3.2.1 Staggered grid layout	69
3.2.2 Non-staggered grid layout	70
3.3 Boundary conditions	72
3.4 Under relaxation	77
3.5 Convergence criteria	77



3.6	Code verification	78
CHAPTER 4.	SIMULATION OF COMPLETE PHASE CHANGE PROCESS USING LOCAL THERMAL EQUILIBRIUM MODEL	80
4.1	Modeling of one-dimensional problems based on modified volumetric enthalpy formulation of two-phase mixture model	80
4.1.1	Problem description and basic assumptions	80
4.1.2	Ranges of parameters	82
4.1.3	Results for the reference case	83
4.1.4	Results obtained with parametric variations for $n=3$	85
4.1.5	Results obtained with parametric variations for $n=1$	87
4.1.6	Transient simulation of complete phase change process	90
4.2	Modeling of one-dimensional problem based on modified enthalpy formulation	92
4.2.1	Ranges of parameters and general remarks	94
4.2.2	Comparison of results for both constant heat flux and wall temperature	96
4.3	Modeling in two-dimensional coordinates using staggered grid layout	100
4.3.1	Problem description and basic assumptions	100
4.3.2	Comparison of one- and two-dimensional models.....	104
4.3.3	Simulation of complete phase change process in channel flow	105
4.3.4	Simulation of complete phase change process in pipe flow	112
4.4	Modeling in two-dimensional coordinates using non-staggered grid layout	115
4.5	Conclusions	116
CHAPTER 5.	SIMULATION OF COMPLETE PHASE CHANGE PROCESS USING LOCAL THERMAL NON-EQUILIBRIUM MODEL	118
5.1	Modeling of one-dimensional problem	118
5.1.1	Problem description and basic assumptions	118
5.1.2	Ranges of parameters	120
5.1.3	Consequence of smoothing of diffusion coefficient	122
5.1.4	Effects of operating conditions	123
5.1.5	Effects of porous media properties	127
5.1.6	Effects of inlet length and partitioning of wall heat flux	130
5.1.7	Results obtained with parametric variations for $n=3$	131
5.2	Modeling in two-dimensional coordinates using staggered grid layout	132
5.2.1	Problem description and basic assumptions	132
5.2.2	Simulation of complete phase change process in channel flow using heat flux at lower wall	134
5.2.3	Transient simulation of complete phase change process in channel flow.....	147



5.2.4	Simulation of complete phase change process in channel flow using heat flux at different locations	151
5.2.5	Simulation of complete phase change process in pipe flow	154
5.3	Modeling in two-dimensional coordinates using non-staggered grid layout	158
5.3.1	Comparison of non-staggered and staggered grids solutions	159
5.3.2	Evaporated volume fraction	161
5.4	Conclusions	162
CHAPTER 6.	SIMULATION OF COMPLETE PHASE CHANGE PROCESS USING ANISOTROPIC MODEL	164
6.1	Problem description and basic assumptions	164
6.2	Ranges of parameters and numerical results	165
6.2.1	Effects of solid thermal conductivity ratio (k_R)	166
6.2.2	Effects of permeability ratio (K_R)	168
6.2.3	Effects of solid thermal conductivity (k_{sx}^*).....	170
6.2.4	Effects of Darcy number (K^*)	172
6.3	Conclusions	175
CHAPTER 7.	SIMULATION OF COMPLETE PHASE CHANGE PROCESS INSIDE DIVERGENT POROUS EVAPORATOR	176
7.1	Problem description and basic assumptions	176
7.2	Ranges of parameters and numerical results	177
7.2.1	Consequence of smoothing of diffusion coefficient	178
7.2.2	Effects of operating conditions	179
7.2.3	Effects of porous media properties	180
7.2.4	Effects of evaporator geometry	180
7.3	Conclusions	181
CHAPTER 8.	CONCLUSION AND RECOMMENDATION	182
8.1	Summary and conclusions.....	182
8.2	Recommendation for future work	187
8.2.1	Inclusion of variable densities in the single phase regions.....	187
8.2.2	Modeling on non-orthogonal coordinates	187
8.2.3	Inclusion of higher order effects	188
8.2.4	Experimental study	188
BIBLIOGRAPHY	189