

# Contents

Acknowledgment	iii
Peer-reviewed Journal Papers	ix
Peer-reviewed Conference Proceedings	xi
Conference and Convention Participations	xiii
Glossary	xv
<b>1 Introduction</b>	<b>1</b>
<b>2 Fundamentals</b>	<b>3</b>
2.1 Laser Basics . . . . .	3
2.1.1 Laser Definition . . . . .	3
2.1.2 General Schematic of the Laser . . . . .	4
2.1.3 Gain Coefficient in Semiconductor Lasers . . . . .	6
2.1.4 Laser Dynamics: Gain and Losses . . . . .	7
2.1.5 Modes in the Optical Resonator . . . . .	7
2.2 External Cavity Diode Laser (ECDL) . . . . .	8
2.3 Ultrashort Optical Pulse Generation . . . . .	9
2.3.1 Principle of Mode Locking . . . . .	9
2.3.2 Passive and Hybrid Mode Locking . . . . .	10
2.3.3 Suppression of Multiple-Pulse Formation . . . . .	12
2.3.4 Timing Jitters of Mode-Locked Lasers . . . . .	12
2.3.5 Self Mode Locking . . . . .	13
2.3.6 Quantum Dot Semiconductor Lasers . . . . .	14
2.3.7 Quantum Dash Semiconductor Lasers . . . . .	15
2.4 Ultrashort Optical Pulse Compressor . . . . .	15
2.5 Ultrashort Optical Pulse Amplification . . . . .	15
2.5.1 Spectral Broadening of Optical Pulses in SC Laser Amplifier	16
2.5.2 Single-pass Amplifier . . . . .	16
<b>3 Femtosecond optical pulse generation from external cavity diode laser geometry based on self-mode-locking regime</b>	<b>19</b>
3.1 Introduction . . . . .	19
3.2 Experimental setup . . . . .	20

3.3	Monolithic gain chip characterization . . . . .	22
3.4	External cavity characterization . . . . .	24
3.5	Pulse evolution . . . . .	24
3.6	Optimum pulse analysis . . . . .	26
3.7	Various repetition-rates analysis . . . . .	27
3.8	Pulsation mechanism and noise analysis . . . . .	28
3.9	Conclusion . . . . .	30
<b>4</b>	<b>Adjustable high repetition-rate femtosecond pulse generation based on injection locking with record pulse stability and broad optical frequency comb without electronic locking</b>	<b>31</b>
4.1	Introduction . . . . .	32
4.2	Locking principle - experimental observation . . . . .	32
4.3	Experimental setup . . . . .	33
4.4	Beat note investigation for external cavity length variation . . . . .	34
4.5	Noise analysis . . . . .	36
4.6	Autocorrelation trace . . . . .	38
4.7	Optical spectrum . . . . .	40
4.8	System operation below 1 GHz external cavity RR . . . . .	40
4.9	Conclusion . . . . .	44
<b>5</b>	<b>Self-mode-locking and passive mode-locking characterization in QD monolithic diode laser - experimental comparison</b>	<b>45</b>
5.1	Introduction . . . . .	45
5.2	Experimental setup . . . . .	46
5.2.1	P-I curves for all mode locking regimes . . . . .	47
5.3	Mode-locking analysis, pulse evolution . . . . .	48
5.3.1	Passive-Mode-locking, conventional . . . . .	48
5.3.2	Passive-Mode-locking, short-circuit mode . . . . .	50
5.3.3	Self-Mode-locking, open-circuit mode . . . . .	51
5.3.4	Self-Mode-locking . . . . .	52
5.4	Pulse: FWHM and width at $1/10$ of the Peak . . . . .	53
5.5	Mode-locking analysis, optical bandwidth . . . . .	55
5.6	Ultrashort pulse generation . . . . .	56
5.6.1	Passive-Mode-locking, conventional . . . . .	56
5.6.2	Passive-Mode-locking, short-circuit mode . . . . .	57
5.6.3	Self-Mode-locking, open-circuit mode . . . . .	58
5.6.4	Self-Mode-locking . . . . .	59
5.7	Optical frequency comb generation . . . . .	61
5.8	Optical feedback influence . . . . .	62
5.9	Conclusion and Outlook . . . . .	64
<b>6</b>	<b>Frequency comb enhancement by the influence of optical feedback based on self-mode-locked diode laser at 1500 nm</b>	<b>65</b>
6.1	Introduction . . . . .	66
6.2	Experimental Setup . . . . .	66
6.3	P-I curves and autocorrelation traces analysis . . . . .	67

---

6.4	Optical frequency comb and pulse-width analysis . . . . .	71
6.5	Noise and optical pulse analysis from the external cavity configuration	75
6.6	Conclusion and Outlook . . . . .	76
<b>7</b>	<b>Noise, RF, and optical pulse investigation of a sub-GHz InP-based 1550 nm monolithic passively and hybrid mode-locked laser chip</b>	<b>77</b>
7.1	Introduction . . . . .	77
7.2	Laser chip and experimental setup . . . . .	78
7.3	Passive mode-locking operation . . . . .	80
7.4	RF investigation . . . . .	81
7.5	Hybrid mode-locking operation . . . . .	84
7.6	Conclusion . . . . .	86
<b>8</b>	<b>Resonant pulse amplification based on mode-locked diode laser at 850 nm</b>	<b>87</b>
8.1	Introduction . . . . .	88
8.2	Experimental Setups . . . . .	88
8.2.1	Master Oscillator . . . . .	89
8.2.2	Master Oscillator Power Amplifier . . . . .	89
8.2.3	Resonant Ring Amplifier . . . . .	90
8.3	Experimental Results . . . . .	91
8.4	Extended analysis - new beam splitter ratio . . . . .	94
8.5	Conclusion and Outlook . . . . .	97
<b>9</b>	<b>Two-photon microscopy based on femtosecond optical pulses generated from edge-emitting mode-locked diode laser</b>	<b>99</b>
9.1	Introduction . . . . .	99
9.2	Experimental setup . . . . .	100
9.3	Experimental results . . . . .	101
9.4	Conclusion . . . . .	104
<b>10</b>	<b>Summary and outlook</b>	<b>105</b>
<b>List of Figures</b>		<b>107</b>
<b>List of Tables</b>		<b>111</b>
<b>References</b>		<b>113</b>
<b>Curriculum Vitæ</b>		<b>127</b>