

Table of Content

Acknowledgments	1
Author's Declaration	2
PUBLICATIONS	3
Table of Content	6
List of Figures	14
List of Tables	28
1 Introduction	29
1.1 Objectives	33
1.2 Thesis Outline	34
2 Literature Review	36
2.1 Previous Work	36
2.2 Summary	40
3 Technical Background	41
3.1 Vegetable Oils	41
3.2 Biodiesel	42
3.3 Fuel stability	48
3.4 Oxidation	49
3.5 Engine oil	57
3.5.1 Oxidation of lubricant base oil	59
3.5.2 Dominant mechanisms of degradation	62
3.6 Oxidative stability of biodiesel and its effect on performance	63
3.7 Entry of fuel into the engine oil	64
3.8 Effect of biodiesel on engine oil	64
4 Basic Experimental Techniques for Evaluation	67
4.1 Techniques for evaluating the suppression of oligomers formation	67
4.1.1 Size Exclusion Chromatography (SEC)	68
4.1.2 Gas Chromatograph-Mass Spectroscopy (GCMS)	69
4.1.3 Total Acid Number or Value (TAN)	69
4.1.4 Viscosity and Density	70

4.1.5	Fourier Transform Infrared Spectroscopy (FTIR)	72
4.1.6	Inductively Coupled Plasma-Mass-Spectrometry (ICP-MS).....	74
4.1.7	Gas Chromatography-Flame Ionization Detector (GC-FID)	75
4.1.8	Induction Period	75
4.1.9	Dielectric property measurement	77
4.1.10	NMR measurement.....	80
5	The focus of the Thesis	82
6	Selection of Adsorbents	88
6.1	Suppression of oligomers formation	88
6.2	The capacity of adsorbents in suppressing Oligomers formation	98
7	Materials and Methods.....	104
7.1	Chemicals.....	104
7.2	Investigated Fuels and Oil	104
7.3	Neat additives.....	108
7.4	Simulated Aging Procedure	109
7.4.1	Laboratory setup apparatus	109
7.4.2	The Metrohm 873 biodiesel Rancimat	111
7.5	Investigation of suppression of oligomer formation.....	111
7.5.1	Linoleic acid methyl ester (C18_2 ME)	112
7.5.2	Rapeseed oil methyl ester (RME)	113
7.5.3	Investigating the effect of the combined adsorbents of magnesium- aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4- hydroxybenzyl) benzene in a ratio of 1:2 respectively on the oil additives	114
7.6	Stabilization of biodiesel and its blends using combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4- hydroxybenzyl) benzene in a ratio of 1:2, respectively	116
7.6.1	Investigating the effect of the combined adsorbents of magnesium- aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4- hydroxybenzyl) benzene in a ratio of 1:2 respectively on oxidative stability of biodiesel and its blends at 170 °C.....	117
7.6.2	Investigating the effect of the combined adsorbents of magnesium- aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4- hydroxybenzyl) benzene in a ratio of 1:2 respectively on oxidative stability of biodiesel and its blends at 110 °C.....	118

7.6.3	Investigating the effect of the combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively on the storage stability of biodiesel and its blends at 40 °C	119
7.7	Measurement techniques	121
7.7.1	Induction period	122
7.7.2	Size Exclusion Chromatography (SEC)	123
7.7.3	Gas Chromatograph-Mass Spectroscopy (GCMS)	124
7.7.4	Total Acid Number (TAN) or Acid value	124
7.7.5	Viscosity and Density	125
7.7.6	Fourier Transform Infrared Spectroscopy (FTIR)	125
7.7.7	Inductively Coupled Plasma-Mass-Spectrometry (ICP-MS)	126
7.7.8	Gas Chromatography-Flame Ionization Detector (GC-FID)	128
7.7.9	Dielectric properties measurement	128
7.7.10	NMR measurement	129
8	Results and Discussion	130
8.1	Investigating the effect of the combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively in suppressing oxidation in base oil blended with linoleic acid methyl ester (C18_2 ME)	130
8.1.1	Gas Chromatography	131
8.1.2	Size Exclusion Chromatography (SEC)	133
8.1.3	FTIR analysis	136
8.1.4	Acid value	143
8.2	Investigating the effect of temperature on the combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively in suppressing oxidation in a blend of 80 % base oil and 20 % rapeseed oil methyl ester	147
8.2.1	Size Exclusion Chromatography (SEC)	147
8.2.2	The acid value of 80 % base oil blended with 20 % RME and treated with and without combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at temperatures of 70 °C, 110 °C, 140 °C and 170 °C with airflow of 10 L/h for 8 h per day for a total of 80 h with Rancimat and compared with the neat unaged blend	152

8.2.3	Effect of adsorbents on the viscosity of 80 % base oil blended with 20 % RME and treated with and without combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at temperatures of 70 °C, 110 °C, 140 °C and 170 °C with airflow of 10 L/h for 8 h per day for a total of 80 h with Rancimat and compared with the neat unaged blend	154
8.2.4	Impact of combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively on the density of 80 % base oil blended with 20 % RME and treated with and without the adsorbents and aged at temperatures of 70 °C, 110 °C, 140 °C and 170 °C with airflow of 10 L/h for 8 h per day for a total of 80 h with Rancimat and compared with the neat unaged blend	157
8.2.5	FTIR evaluation of neat and aged 80 % base oil blended with 20 % RME and treated with and without combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at temperatures of 70 °C, 110 °C, 140 °C and 170 °C with airflow of 10 L/h at 8 h per day for 80 h with Rancimat	160
8.3	Investigating the effect of the amount of combined adsorbents magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively in suppressing oxidation in rapeseed oil methyl ester and base oil blend	170
8.3.1	GCMS analysis of 80 %base oil blended with 20 % RME biodiesel treated with and without combined adsorbents magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at 170 °C with airflow of 10 L/h at 8 h per day for a total of 80 h using the Rancimat	170
8.3.2	Size exclusion chromatography (SEC) analysis of 80 %base oil blended with 20 % RME biodiesel treated with and without combined adsorbents magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at 170 °C with airflow of 10 L/h for 80 h using the Rancimat	174
8.3.3	Acid value	179
8.3.4	Viscosity.....	181
8.3.5	Density.....	185
8.3.6	FTIR evaluation of 30 mL 80 %base oil blended with 20 % RME biodiesel treated with and without various amounts of combined adsorbents magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at 170 °C with airflow of 10 L/h for 80 h using a Rancimat	186

8.3.7	Impact of adsorbents on metallic oil additives.....	193
8.3.8	Impact of adsorbent on organic additives in the oil	199
8.4	Using combined adsorbents of magnesium-aluminum hydrotalcite and 1, 3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively to cause stabilization of biodiesel and its blends at 170 °C	208
8.4.1	SEC analysis of biodiesel blends (20 %RME mixed with 80 %diesel fuel) treated with and without 1 g combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at 170 °C with airflow of 10 L/h using a Rancimat.....	208
8.4.2	GCMS analysis of 80 %diesel fuel mixed with 20 %RME treated with and without combined 1 g adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at 170 °C with airflow of 10 L/h for 48 h at 8 h per day using a Rancimat.....	212
8.4.3	The total acid value of 80 %diesel fuel mixed with 20 %RME treated with and without combined 1 g adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at 170 °C with airflow of 10 L/h for 48 h at 8 h per day using a Rancimat.....	214
8.4.4	Results of viscosity of 80 %diesel fuel mixed with 20 %RME treated with and without combined 1 g adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at 170 °C with airflow of 10 L/h for 48 h at 8 h per day using a Rancimat.....	216
8.4.5	Effect of combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively on the density of 80 %diesel fuel mixed with 20 %RME and aged at 170 °C with airflow of 10 L/h for 48 h at 8 h per day using a Rancimat.....	220
8.4.6	Interrelationships between acid value, viscosity, and density of 80 %diesel fuel mixed with 20 %RME treated with and without combined 1 g adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at 170 °C with airflow of 10 L/h for 48 h at 8 h per day using a Rancimat.....	222
8.4.7	FTIR analysis of 80 %diesel fuel mixed with 20 %RME treated with and without combined 1 g adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at 170 °C with airflow of 10 L/h for 48 h at 8 h per day using a Rancimat.....	225

8.5	Stabilization of biodiesel and its blends at 110 °C using 0.225 g combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2, respectively	231
8.5.1	Induction period measurements	232
8.5.2	SEC analysis of 30 mL 20 % RME mixed with 80 % diesel fuel treated with and without 0.225 g combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively using a Rancimat at 110 °C with airflow of 10 L/h at 8 h per day	233
8.5.3	Effect of combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively on the acid value of 20 %RME and 80 % diesel fuel blend during the oxidation process	235
8.5.4	Impact of combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively on the viscosity of biodiesel blend during aging at 110 °C	237
8.5.5	Analysis of the impact of combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively on the density of biodiesel blend during aging at 110 °C 240	
8.5.6	Relationship between viscosity and an acid value of 20 % RME mixed with 80 % diesel fuel and treated with and without combined 0.225 g adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at 110 °C with airflow of 10 L/h for durations of 20 h, 40 h, 60 h, and 80 h at 8 h per day using a Rancimat.....	242
8.5.7	FTIR analysis of 30 mL 20 % RME mixed with 80 % diesel fuel and treated with 0.225 g combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and aged at 110 °C with airflow of 10 L/h at 8 h per day for durations of 20 h, 40 h, 60 h and 80 h using a Rancimat.....	244
8.6	Investigating the effect of the combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively in stabilizing rapeseed oil methyl ester and its blends during long term storage conditions	252
8.6.1	Evaluation of induction period of neat biodiesel	252
8.6.2	The induction period of biodiesel blends.....	253
8.6.3	SEC analysis of aged 40 mL of 80 %diesel fuel blended with 20 %RME treated with and without 0.675 g of combined adsorbents of magnesium-aluminum	

hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and stored at 40 °C in an oven from 0 up to 120 days 255	
8.6.4 Assessment of total acid values of 40 mL of biodiesel treated with and without 0.675 g of combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively stored at 40 °C from 0 up to 120 days.....	256
8.6.5 Evaluation of total acid values of 80 %diesel fuel blended with 20 %RME treated with and without 0.675 g of combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and stored at 40 °C from 0 up to 120 days	258
8.6.6 Impact assessment of combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively on the viscosity of 80 % diesel fuel blended with 20 %RME	260
8.6.7 Investigation of the effect of the combined adsorbents of 0.675 g magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively on the density of 40 mL 80 % diesel fuel blended with 20 %RME stored in an oven at 40 °C for 120 days.....	263
8.6.8 FTIR analysis of neat biodiesel treated with and without combined 0.675 g adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and stored at 40 °C in the oven for up to 120 days	266
8.6.9 FTIR analysis of biodiesel blends, 80 %diesel fuel mixed with 20 %RME treated with and without combined 0.675 g adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively and stored at 40 °C in an oven for up to 120 days....	268
8.7 Confirmation of suppression of oligomers formation.....	272
8.7.1 Effect of 0.675 g combined adsorbents of magnesium-aluminum hydrotalcite and 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl) benzene in a ratio of 1:2 respectively on relative permittivity of 80 % base oil blended with 20 % RME and aged at 170°C	272
8.7.2 The dissipation factor.....	275
8.7.3 Acid value	276
8.7.4 NMR.....	278
9 Conclusion, outlook, and recommendation	289
9.1 Conclusion.....	289

9.2 Outlook and Recommendation	293
Bibliography	295
10 Appendix.....	322
11 Glossary.....	331