



Contents

| | |
|---|-----------|
| Nomenclature | 9 |
| 1. Introduction | 17 |
| 2. State of the Art | 19 |
| 2.1. Ultrafine grinding in stirred media mills | 19 |
| 2.2. The limit of grinding | 20 |
| 2.3. Graphene - properties and production methods | 26 |
| 3. Theoretical Background | 31 |
| 3.1. Wet grinding with stirred media mills | 31 |
| 3.1.1. Fundamentals in stirred media milling | 31 |
| 3.1.2. The concept of stress energy and stress number | 32 |
| 3.1.3. Stabilization methods | 34 |
| 3.2. The particles' microstructure | 38 |
| 3.2.1. Defect structures in crystalline matter | 38 |
| 3.2.2. Size effects in nanocrystalline materials | 40 |
| 3.3. Particle breakage | 43 |
| 3.3.1. General considerations | 43 |
| 3.3.2. Breakage theories | 46 |
| 3.3.3. Fracture along the length scales | 48 |
| 4. Experimental Section | 51 |
| 4.1. Experimental setup | 51 |
| 4.1.1. Comminution in LabStar LS1 | 51 |
| 4.1.2. Delamination in Batch Mill PE 075 | 53 |
| 4.1.3. Dry grinding in a planetary ball mill | 54 |



| | |
|---|------------|
| 4.2. Materials and methods | 54 |
| 4.2.1. Materials | 54 |
| 4.2.2. Characterization methods and sample preparation | 56 |
| 5. Breakage Behavior of Nanoparticles | 61 |
| 5.1. The apparent and true grinding limit | 61 |
| 5.2. The breakage behavior of tin dioxide | 64 |
| 5.2.1. Evolution of external structure | 64 |
| 5.2.2. Evolution of internal structure | 68 |
| 5.2.3. TEM studies of SnO ₂ | 72 |
| 5.2.4. Breakage mechanism of tin dioxide | 77 |
| 5.3. Influence of feed material | 80 |
| 5.4. Influence of process conditions | 82 |
| 5.4.1. Influence of stress energy | 82 |
| 5.4.2. Breakage mechanisms at different SE | 86 |
| 5.4.3. Influence of grinding media shape | 89 |
| 5.4.4. Influence of suspension viscosity | 91 |
| 5.4.5. Influence of suspension stability | 94 |
| 5.4.6. Influence of process temperature | 95 |
| 5.4.7. Conclusion of process variations | 97 |
| 5.5. Breakage behavior of various inorganic materials | 98 |
| 5.5.1. Milling behavior of zirconia and alumina | 98 |
| 5.5.2. Comparison of different materials | 105 |
| 5.5.3. Grinding limit as a result of machine limitation | 108 |
| 5.5.4. Phase transition during grinding | 109 |
| 5.6. Scale-up of nanomilling | 111 |
| 5.7. The limit in dry grinding processes | 114 |
| 6. Delamination of Graphite | 121 |
| 6.1. Breakage behavior of graphite | 122 |
| 6.1.1. Preliminary experiments | 122 |
| 6.1.2. Mechanism of delamination | 125 |
| 6.2. Characterization of delaminated sheets | 131 |
| 6.3. The role of stress energy | 139 |
| 6.4. Yield of delaminated sheets | 142 |



Contents

| | |
|--|------------|
| 6.5. First examples of application | 145 |
| 6.5.1. Production of filled polymers | 145 |
| 6.5.2. Preparation of conductive films | 148 |
| 6.5.3. Coating of delaminated sheets with platinum nanoparticles | 152 |
| 7. Conclusion and Outlook | 157 |
| Bibliography | 160 |
| A. Appendix | 173 |
| A.1. Reproducibility of grinding experiments | 173 |
| A.2. Comparison between Rietveld and Scherrer evaluation | 176 |
| A.3. Micropore analysis of various materials | 179 |
| A.4. Coating of delaminated graphite sheets | 182 |