



Contents

1	Introduction	1
2	Fundamentals	5
2.1	Ferromagnetism	5
2.1.1	Origin of ferromagnetism	5
2.1.2	Magnetic anisotropy	8
2.1.3	Vector fields for the macroscopic description	12
2.1.4	Domain theory	13
2.1.5	Stoner-Wohlfarth model	18
2.1.6	Magnetization reversal by curling	20
2.1.7	Micromagnetism	21
2.2	Domain walls in ferromagnetic nanowires	23
2.2.1	Preparation of domain walls	23
2.2.2	Depinning and motion of domain walls	27
2.3	Magnetoresistive effects	29
2.3.1	Spin-dependent transport	29
2.3.2	Lorentz magnetoresistance	31
2.3.3	Negative magnetoresistance	31
2.3.4	Anisotropic magnetoresistance	31
2.3.5	Domain-wall resistance	32
2.4	X-ray magnetic circular dichroism	33
3	Micromagnetic simulations	35
3.1	Method	35
3.2	Examples	39
3.2.1	Magnetic states of a tube	39
3.2.2	Demagnetization fields, nucleation, and reversal modes in cylindrical wires	40
4	Methods	45
4.1	Synthesis of cylindrical nanowires and sample preparation	45
4.2	Magnetoresistance measurements	48
4.3	Magnetic force microscopy	58
4.4	Photoemission electron microscopy	62



5	Magnetization reversal in cylindrical nickel nanowires	73
5.1	Magnetization reversal in straight nickel nanowires and the curling model	74
5.2	Experimental results	90
6	Preparation of domain walls in cylindrical nanowires	109
6.1	Ion irradiation	109
6.2	Bent wires	116
6.3	Diameter-modulated wires	120
7	Magnetization reversal in Co/Pt wires with perpendicular magnetic anisotropy	143
8	Conclusion	151
A	Publications	155
A.1	Magnetic reversal of cylindrical nickel nanowires with modulated diameters	155
A.2	Domain-wall pinning and depinning at soft spots in magnetic nanowires	162
B	Experimental details	167
B.1	Synthesis parameters for cylindrical wires	167
B.1.1	Nickel wires with one diameter modulation	167
B.1.2	Nickel-iron wires with one diameter modulation	168
B.1.3	Nickel wires with three modulations	168
B.2	Wafer substrates	169
B.3	Electron-beam lithography	170
B.3.1	Process parameters	170
B.3.2	Definition of contacts on self-arranged nanostructures	172
B.4	Optical projection lithography	174
B.5	Parameters for RF-plasma and sputter deposition	175
B.6	Transmission x-ray microscopy	176
B.6.1	Setup	176
B.6.2	Magnetic imaging of cylindrical nickel nanowires	177
B.7	Procedure for the elimination of thermal drift in Fig. 5.11(b)	178
B.8	Magnetization reversal in cobalt-nickel nanowires	179
	Bibliography	181