



Contents

1	Introduction and motivation	1
1.1	Probing the universe	1
1.1.1	Short historical background and discovery of the interstellar medium	1
1.1.2	Interstellar molecules, chemical networks and star formation - Tracers and spectral resolution	3
1.1.3	Comparison of recent and future observational experiments and receiver developments at KOSMA - Need for array compatible heterodyne detectors at 1 THz	5
1.2	Photon detectors for radio astronomy - Arrays and fundamental sensitivity	10
1.2.1	Coherent and incoherent detection	10
1.2.2	Superconductive waveguide mixers on silicon membranes	14
1.3	Integrated detectors for heterodyne arrays	19
1.3.1	Balanced SIS mixers	19
1.3.2	Terahertz niobium SIS mixers with a niobium-titanium-nitride superconducting tuning circuit and a normal-metal energy-relaxation layer	20
2	Mesoscopic detector elements	25
2.1	Linear-response theory, fluctuation-dissipation theorem and detector sensitivities	25
2.1.1	Fundamental sensitivity limit in detector arrays	38
2.2	Theories of superconductivity	43
2.2.1	Ginzburg-Landau theory of superconductivity in clean and disordered systems: coherence length, magnetic penetration-depth and supercurrent	43
2.2.2	The microscopic theory of Bardeen-Cooper-Schrieffer	51
2.2.3	Interactions between quasiparticles in superconductors and normal metals	60
2.3	Quasiclassical quantum field theory in superconductors	69
2.3.1	Green's functions of superconductivity	69
2.3.2	Dirty superconductors I - The quasiclassical limit	73
2.3.3	Dirty superconductors II - Superconducting correlations in superconductor/normal metal proximity systems and boundary conditions	77
2.3.4	Results for NbTiN/Au bilayer structures	85



3	Design of planar superconducting transmission-lines and circuits	89
3.1	Microwave response of superconductors	89
3.1.1	Complex conductivity - Mattis-Bardeen theory	89
3.1.2	Complex conductivity in proximity and disordered superconductors - Nam theory	95
3.1.3	Superconducting transmission-lines	97
3.2	Balanced-mixer components design	109
3.2.1	Two-junction tuning circuit	109
3.2.2	Current density and tuning-circuit bandwidth	112
3.2.3	Commercial electromagnetic design software packages and their applicability for superconducting circuit engineering	113
3.2.4	Broadband tapered-slotline waveguide antennas	114
3.2.5	380-520 GHz coplanar waveguide 90° RF hybrid-coupler	119
3.2.6	Superconductor-insulator-superconductor circuit and alternating impedance transformer	123
3.2.7	Three-stage coplanar waveguide RF blocking-filter	127
3.2.8	Electromagnetic-field simulation of the balanced-mixer circuit in two different waveguide environments	130
3.2.9	An IF circuit-board for the first experiments	133
4	Experimental setup and measurement procedure	135
4.1	Balanced-mixer dewar assembly	135
4.1.1	Waveguide-mixer block assembly and IF circuit-board	139
4.2	Balanced-mixer device chip fabrication	143
4.3	Setup schematic and general measurement procedure	145
4.3.1	Modification of the calibration blackbody-temperatures due to dielectric dewar-windows, IR filters and the beamsplitter	148
5	Characterization of 400-500 GHz planar-circuit balanced SIS mixers in two waveguide geometries	153
5.1	Introduction and comparison to related work	154
5.2	Measurement procedure and data analysis	155
5.3	The non-ideal balanced-mixer device	160
5.3.1	Effect of low NR value on the Y factor	166
5.4	Mixer characterization measurements	166
5.4.1	Balanced-mixer device in a step-discontinuity waveguide mixer-block using a Gunn-driven local-oscillator source	167
5.4.2	Balanced-mixer device in a continuous-waveguide mixer-block using a synthesizer-driven local-oscillator source	172
5.5	Conclusion	178
6	Balanced SIS mixer as an input-noise meter	181
6.1	Introduction	182
6.2	LO input noise-temperature measurements	184
6.3	Influence of increasing LO near-carrier noise power on $T_{rec}(\nu)$	196
6.4	Conclusion	199



7	Improved Nb SIS devices for heterodyne mixers between 700 GHz and 1.3 THz	201
7.1	Introduction	201
7.2	Device design and conceptual background	203
7.3	Device variations and measurement setup	208
7.3.1	Fabrication	208
7.3.2	Measurement setup	210
7.4	Experimental results and analysis	210
7.5	Possible adverse effects due to inserted normal metal layer	219
7.6	Conclusion	220
7.7	Additional material	221
8	Conclusion and Outlook	225
A	Properties of noise and measurement methods	231
A.1	Wiener-Khinchin theorem and noise-power spectral density	231
A.1.1	Classical formalism	231
A.1.2	Quantum formalism	233
A.1.3	Theorems	234
A.2	Measurement of noise-power spectral density	235
A.2.1	Square law detector - Classical calculation	235
A.2.2	Incoherent detector - Quantum calculation	236
B	Electromagnetic wave propagation in a dielectric medium	241
B.1	Definitions and assumptions	241
B.2	Poynting theorem in a homogeneous lossy medium	242
B.3	Propagation-matrix formalism	244
B.4	Matching of an electromagnetic field across an interface	245
B.5	Multiple scattering at two dielectric interfaces	247
B.6	Fresnel formulas - General case of arbitrary incident angle	248
C	Balanced-mixer characterization measurement results	251
C.1	Continuation of section 5.4.1	251
C.1.1	Heterodyne measurements with same mixer bias-polarity	251
C.1.2	Heterodyne measurements with opposite mixer bias-polarity	256
C.2	Continuation of section 5.4.2	261
C.2.1	Heterodyne measurements with opposite mixer bias-polarity	261
	References	266
	Acknowledgement	281
	Financial support	285
	Erklärung	287
	Lebenslauf	289