



Xuan Luo (Autor)

Determination of a suitable mud window under HM and THM-coupled conditions in real-time



<https://cuvillier.de/de/shop/publications/7056>

Copyright:

Cuvillier Verlag, Inhaberin Annette Jentsch-Cuvillier, Nonnenstieg 8, 37075 Göttingen, Germany
Telefon: +49 (0)551 54724-0, E-Mail: info@cuvillier.de, Website: <https://cuvillier.de>



Table of Contents

Acknowledgements	iii
List of Figures	vi
List of Tables	xi
Abstract	xiii
1. Introduction.....	1
1.1. Objectives	1
1.2. State-of-the-art	2
1.3. Thesis subjects	4
2. Models to calculate a suitable mud window	6
2.1. Coupled effects governing the stress distributions around wellbore	12
2.2. Wellbore stability evaluation criteria	13
2.2.1. Criterion to determine RTFG	14
2.2.2. Criterion to determine FG	17
2.2.3. Criterion to determine SFG.....	18
3. Sensitivity analysis.....	23
3.1. Introduction.....	23
3.2. Methods.....	24
3.3. Results.....	27
3.3.1. The “must-have” group.....	34
3.3.2. The “high-sensitive” group	35
3.3.3. The “low-sensitive” group	35
3.4. Conclusions.....	36
4. Methods to determine UCS, IFA and PPG.....	37
4.1. Introduction.....	37
4.2. Determination of uniaxial compressive strength (UCS)	37
4.3. Determination of internal friction angle (IFA).....	39
4.4. Determination of formation pore pressure	39
5. Determination of primary in-situ stresses using borehole breakout and acoustic measurements.....	41
5.1. Introduction.....	41
5.2. Estimation of primary in-situ stresses from borehole breakout	41
5.2.1. Definition of Borehole Breakout	41
5.2.2. Building mechanisms of borehole breakout	42
5.2.3. Calculation of in-situ stresses based on breakout shape	44
5.2.4. Case study: calculation of in-situ stresses based on breakout shape	45
5.3. Estimation of primary in-situ stresses from sonic logging	46
5.3.1. Sonic logging and shear wave splitting	46
5.3.2. Relationship between wave velocity and loading conditions	50
5.3.3. Methods to calculate the horizontal stresses based on shear wave splitting.....	54
5.3.4. Determination of coupling coefficients.....	54
5.3.5. Case study: calculation of in-situ stresses based on shear wave splitting.....	59
5.4. Conclusions.....	61



6.	Calculation of Biot's coefficient from well logs.....	62
6.1.	Introduction.....	62
6.2.	Existing correlation methods to calculate of Biot's coefficient (Method 1).....	63
6.3.	Calculation of Biot's coefficient with dynamic rock and solid compressibility	63
6.3.1.	Calculation of solid wave velocities using own developed empirical equation (Method 2)	64
6.3.2.	Calculation of solid wave velocities using V_p/V_s ratio (Method 3).....	69
6.4.	Case study	72
6.4.1.	Method 1	72
6.4.2.	Method 2	73
6.4.3.	Method 3	74
6.5.	Comparison of the three methods	75
6.6.	Conclusions.....	76
7.	Simulation of the temperature profiles	78
7.1.	Introduction.....	78
7.2.	Semi-analytical calculation method.....	79
7.2.1.	Finite differential calculation of temperature distribution in rock formation	82
7.2.2.	Calculation of heat exchange between annulus, tubing and formation	83
7.2.3.	Simulation of the circulation process.....	83
7.2.4.	Calculation of thermal stress using numerical integration.....	84
7.3.	Model verification.....	84
7.3.1.	Comparison with analytical solution after Ramey (1962)	84
7.3.2.	Comparison with the measured outlet temperature	86
7.4.	Principle of the injected mud temperature	89
7.5.	Scenario simulation.....	91
7.5.1.	Temperature profile for Case B.....	92
7.5.2.	Temperature profile for Case C.....	96
7.5.3.	Influence of parameter a^T and the initial mud temperature on bottomhole temperature (Case C)	96
7.6.	Calculation of thermal stress.....	101
7.7.	Conclusions.....	107
8.	Case studies.....	108
8.1.	Mud window considering HM-coupled effects	110
8.2.	Mud window considering THM-coupled effects	112
9.	Conclusions and outlook.....	122
	References	125
	Appendix	133
	Nomenclature	136