



Alireza Bastani (Autor)  
**Bondability of modified wood**



<https://cuvillier.de/de/shop/publications/7282>

Copyright:  
Cuvillier Verlag, Inhaberin Annette Jentsch-Cuvillier, Nonnenstieg 8, 37075 Göttingen,  
Germany  
Telefon: +49 (0)551 54724-0, E-Mail: [info@cuvillier.de](mailto:info@cuvillier.de), Website: <https://cuvillier.de>



## Table of content

|  |    |
|--|----|
| <b>1. Summary</b> .....                                  | 1  |
| <b>2. Introduction</b> .....                             | 5  |
| <b>2.1. Wood and adhesion</b> .....                      | 5  |
| 2.1.1. Wood; a natural, renewable raw material.....      | 5  |
| 2.1.2. Furniture and building constructions.....         | 5  |
| 2.1.3. Adhesion background and theories.....             | 6  |
| 2.1.4. Influencing factors on bonding.....               | 8  |
| 2.1.5. Evaluation methods.....                           | 9  |
| <b>2.2. Wood modification</b> .....                      | 11 |
| 2.2.1. Background, description and examples.....         | 11 |
| 2.2.2. Modified species.....                             | 13 |
| 2.2.3. Furfurylation.....                                | 13 |
| 2.2.4. Melamine treatment.....                           | 15 |
| 2.2.5. Thermal modification.....                         | 17 |
| 2.2.6. Phenol treatment.....                             | 19 |
| <b>2.3. Bonding of modified wood and adhesives</b> ..... | 19 |
| 2.3.1. Bonding of modified wood.....                     | 19 |
| 2.3.2. Wood adhesives.....                               | 21 |
| 2.3.2.1. EPI.....  | 23 |
| 2.3.2.2. PVAc.....                                       | 23 |



|   |           |
|---|-----------|
| 2.3.2.3. PU.....  | 24        |
| 2.3.2.4. PF.....  | 25        |
| 2.3.2.5. PRF.....   | 26        |
| <b>2.4. Aim of Study.....</b>   | <b>26</b> |
| <b>2.5. Evaluation methods used in this research.....</b>   | <b>28</b> |
| <b>2.5.1. Evaluation of the wood surface and water related properties.....</b>  | <b>28</b> |
| 2.5.1.1. Capillary water uptake.....  | 28        |
| 2.5.1.2. Contact angle measurement.....   | 30        |
| 2.5.1.3. Surface energy of the wood.....  | 31        |
| <b>2.5.2. Optical evaluation.....</b>   | <b>32</b> |
| 2.5.2.1. Light and fluorescence microscopy.....   | 32        |
| 2.5.2.2. X-ray micro-computed tomography.....   | 35        |
| <b>2.5.3. Evaluation of mechanical properties.....</b>  | <b>37</b> |
| <b>3. Results and discussion.....</b>   | <b>38</b> |
| 3.1. Evaluation of the effects of phenol formaldehyde modification of the beech wood on its bonding performance.....    | 38        |
| 3.2. Water uptake and wetting behaviour of furfurylated, N-methylol melamine modified and thermally modified wood.....  | 39        |
| 3.3. Gross adhesive penetration in furfurylated, N-methylol melaminemodified and thermally modified wood.....           | 41        |
| 3.4. Study of adhesive bondlines in modified wood with fluorescence microscopy and X-ray micro-computed tomography..... | 44        |



|  |           |
|--|-----------|
| 3.5. Shear strength of furfurylated, N-methylol melamine and thermally modified wood bonded with three conventional adhesives.....               | 46        |
| 3.6. Effect of open assembly time and equilibrium moisture content on the penetration of polyurethane adhesive into thermally modified wood..... | 48        |
| 3.7. Development of bonding strength of modified birch veneers during adhesive curing.....   | 51        |
| <b>4. Conclusions and further studies.....</b>   | <b>53</b> |
| <b>5. References.....</b>  | <b>56</b> |
| <b>6. Publications.....</b>  | <b>64</b> |